I0A005600310004-5
REPORT
CD NO.
DATE DISTR 13 Fanuary 1955
NO OF PAGES 2 25X1
NO. OF ENCLS USTED BELOW: 25X1
SUPPLEMENT TO REPORT NO

25**X**1

12	The same of the sa
	THIS OCCUBENT CONTAINS INFORMATION AFFECTIVE THE NATIONAL DEFINIS OF THE UNITED STATES, WITHIN THE BEARING OF THEM IS, SECTIONS 728 WHO 744, OF WHE U. S. CODE, AS ALERDOS. ITS TRANSLESSION OR REVEL NATION OF ITS CONTENTS TO OR RECEIPT BY ALE THE OFFICE OF THE OFFI S PROMISTED BY LAW YILL REPRODUCTION OF THIS FORM IS PROMISTED.
ì	AND 784, OF THE U. S. CODE, AS ARENDED. ITS TRANSMISSION OF REVEL.
ij	S PROBLETTED BY LAW THE REPRODUCTION OF THIS FORM IS PROBLETTED.
(A)	Management of the American State of the Control of

COUNTRY SUBJECT

PLACE ACQUIRED DATE OF INFO.

ARMY

THIS IS UNEVALUATED INFORMATION

- 1. The establishment of new Trattendorf Combine was planned in August 1954. This combine was to have a daily capacity of 15,000 tons of briquettes and a power station with an output of 50,000,000 watts which would eventually be enlarged. In addition, there was to be a coking plant for high temperature (HT) coke to which a tar processing plant would be added. This tar processing plant would possibly have a production of 500,000 tons of low-temperature lignite tar.
- 2. According to suggestions previously made by Dr Georg Bilkenroth, HT-production would be increased to meet the demands for higher capacities of the metallurgical industry. It has become possible to raise the quality of coke to such ε degree by the introduction of several improvements in the processing technique that any objections on the part of the metallurgical industry may be considered virtually unfounded. This new HT coking plant was to reach the capacity originally scheduled for Lauchhammer, or a yearly output of 2,400,000 tons. In the future, the cake production in Trattendorf would necessarily be subjected to a particularly close examination because the coal deposits there differ structurally from those in Lauchhammer.
- 5. It will not be possible to put the first sections of the Trattendorf Combine into operation according to plan, as early as 1957, because of the curtailment of the investment funds. Even the 1955 investment funds will probably be struck from the investment plan, because the targets of the capacities schedular for 1954 could not be met because of considerable backlogs in the production of the machine industry and the rise in prices.

 25X1
- 4. It was planned to rename the new combine at Trattendorf
 Schwarze Pumpe (Black Pump) for the place located 3 kilometers
 south-southwest of Spremberg.


Comment. According to the 1954 economic plan, the Lauchhammer coking plant was scheduled to produce a total of 400,000 tons of high-temperature cold (HT coke) for use at the EWW in Calbe/Saske.

Should at estually be possible to produce 2,400,000 tons of coal usable for industrial surposes from lignite, East Germany would become largely independent of imports of hard coal coke.

25X1

CLASSIFICATION			SSIFICATIO	N	SECRET	
8	NAVY	X	NSRB		DISTRIBUTION	
ď	AIR	#x	FBI			<u> </u>

15



Approved For Release 2007/09/19: CIA-RDP80-00810A005600310004-5 CLASSIFICATION SECRET CENTRAL INTELLIGENCE AGENCY REPORT GD NO. DATE DISTR. COUNTRY 13 January 1955 Bast Germany NO. OF MOES New Trattenderf Combine SUBJECT 25X1 PLACE ACQUIRED SUPPLEMENT TO DATE OF REPORT NO. INFO. 25X1 THIS IS UNEMALUMPED INFORMATION The establishment of new Trattendorf Combine was planned in August 1954.
 This combine was to have a daily capacity of 15,000 tens of briquettes and a power station with an output of 50,000,000 watts which would eventually be emigrged. In addition, there was to be a coking plant for 25X1 high temperature (ET) coke to which a ter processing plant would be added. This tar presessing plant would possibly have a production of 500,000 tons of low-temperature ligaite tar. reviously made by Dr Georg Billsareth, HT-production According to suggestions reald be increased to mee r higher capacities of the metallurgical industry. essible to raise the quality of of several improvements in the coke to di of the metallungical inda w ET coking plant mer, or a yearly output of 2/400,000 tends in the famile, the come production in Trattender's would necessarily be subjected to a particularly close examination because 25X1 the seal deposits there differ structurally from these in Lauchhammer. 3. It will not f the Trattendorf Combine into operati ecouse of the curtailment of the inve mis will probably be struck from the law of the capacities 25X1 scheduled for 1954 the production of Spremberg. Councest. Ascerding to the 195 rie plan, the Lauchke coking plant was scheduled to pred 400,400 tems of high-tem cole (ET cole) for use at the new to della Junte. In addition coke made from hard seel arrived there from Unper Stleets and the EKS in becatembers/Suer also personally used small quantities of hir coas from Lauchhammer. Small it actually be pessible to produce 2,400,000 tens of coal usable for industrial purposes from lignite, East Sermany would become largely independent of

A.

